



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

313L

Applications



PRODUCT SPECIFICATIONS

Certifications:

Meets ANSI A156.6 for J401 pull and ANSI A156.6 for J407 pull plate

Clearance:

1-5/8" (41mm)

Door Thickness:

1-3/4" - 2" (45mm - 51mm)

Finishes:

US32D

H Height:

11" (279mm)

Material:

11 GA stainless steel

Notes:

For use with many exit devices

Thru bolts directly to device

Must order cylinders separately

When mounting trim to a Hager exit device, retaining cup (2-649-0137) must be purchased to ensure proper installation and a 7/16" (11mm) tall cylinder collar must be purchased when using a 1-1/4" to 1-3/8" (32mm - 35mm) long rim cylinder (See instructions for more detail)

Hardware:

Dummy - four 1/4" - 20 x 3/4" FPHMS and four finish washers

Mortise lock - four 1/4" - 20 x 3/4" FPHMS and four finish washers

Exit device - supplied with exit device

Options:

Cylinder cutout available [1-1/4" (32 mm) diameter standard for exit device use and 1-1/2" (38 mm) diameter standard for mortise lock use]

Projection:

1-7/8" (478mm)

Size:

7-13/32" x 11" (188 mm x 280mm)