



## 4700 RIM

### 4700 Series Grade 1 Rim Exit Device

#### Applications

Commercial



#### PRODUCT SPECIFICATIONS

##### Certifications:

ANSI/BHMA A156.3-2014 Grade 1  
UL305 Listed for panic hardware  
UL/cUL Listed for up to 3 hours for "A" labeled doors  
UL10C Positive Pressure Rated  
UL10B Neutral Pressure Rated  
Warnock Hersey listed for up to 3 hours with fire rated removable mullion  
Complies with ANSI 117.1 for accessible buildings and facilities

##### Cover:

Cast brass, bronze, stainless steel, zinc

##### Cover Tube:

Painted steel, plated steel, stainless steel

##### Dogging:

Hex key dogging standard on panic-rated devices

##### Door Thickness:

1-3/4" (44 mm) - standard

##### Door Width:

36" (914mm) field sizeable to 30" (762 mm) door  
48" (1219mm) field sizeable to 36" (914 mm) door

##### End Caps:

Painted steel, plated steel, stainless steel

##### Fasteners:

Wood and machine screws,  
Thru-bolts

##### Finishes:

US3, US32D, ALM, DBZ

##### Functions:

Cylinder Escutcheon 08  
Blank Escutcheon 14  
Night Latch 03  
Dummy 02

##### Latchbolt Type:

5/8" (16mm) throw, pullman type with automatic dead-latching,  
stainless steel

##### Notes:

Cylinders sold separately,  
Recommended to be used on appropriately reinforced doors  
Ideal for heavy duty commercial applications

##### Projection:

2-7/16" (62mm) in undogged position  
1-3/16" (30mm) in dogged position

##### Stile Width:

4-1/2" (114mm) - minimum stile width required for single door and  
5/8" (16mm) stop  
4-1/2" (114mm) - minimum stile width required for double door x  
surface vertical rod device with double door strike  
5" (127mm) - minimum stile width required for double doors with  
2" (51mm) mullion  
All stile widths are measured from door edge

##### Strikes:

Stainless steel with plated roller - included standard with panic  
devices  
Solid stainless steel - included standard with fire-rated devices  
Surface applied to frame with slotted holes for easy adjustment  
Optional double door strike for use with surface vertical rod and rim  
devices

##### Trim:

Archer, August, or Withnell lever with escutcheon  
Archer, August, Withnell lever with key-in-lever trim  
Raised lip pull  
Pull plate trim  
Rim cylinder x optional pull

##### Warranty:

Five-years