



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

9852HD

Applications

For 2' x 6' walls



PRODUCT SPECIFICATIONS

Case Quantity:

1

Certifications:

Meets performance requirements of ANSI/BHMA 156.14 (Grade 1) for sliding doors by exceeding 100,000 cycles in operation.

Type: D02311-250

ADA Compliant

Door Specifications:

For doors 1-3/8" - 1-3/4" (35 mm - 44 mm) thick, up to 3'0" (914 mm) wide and 6'8" (2032 mm) high, For doors weighing up to 250 lbs. (113 kg)

Door Thickness:

For doors 1-3/8" - 1-3/4" (35 mm - 44 mm) thick

Installation:

For Bi-Parting Doors use Hager Double Pocket Door Kit 9639 (sold separately,

Joins 2 pocket door frames to make one large doorway. Rough opening width changes to 4 times one door width

Maximum Door Weight:

250 lbs. (113 kg)

Options:

Soft Close mechanism (1-269-8651) is available, sold separately.

See Related Files for additional information.

Specifications:

Heavy-Duty, V-groove, jump-proof aluminum track, Pre-assembled header assembly goes up quickly, Easy door installation and removal for painting and repair, 3 pair of wood split studs with wood inserts • size 3/4" (19 mm) x 1-5/8" (26 mm) length relative to height • steel encased for rigidity and to prevent fastener penetration into the pocket Track header unit attaches to rough framing at both ends, Split studs can be nailed or screwed to track header