



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

4900XF

4900XF

Fire-Rated Keyed Removable Mullion Set

Applications

For use with 4500, 4600, and 4700 Series rim exit devices on fire-rated pairs of doors.



PRODUCT SPECIFICATIONS

Available Sizes:

84" (2134 mm)

96" (2438 mm)

Certifications:

UL/cUL listed for up to 3 hours for "A" label single doors

UL 10C Positive Pressure Rated

UL 10 B Negative Pressure Rated

Cylinders/Cores:

Solid brass 6-pin rim cylinders, 3901, sold separately.

Conventional cylinder, C keyway - Standard, sold separately.

Small Format Interchangeable Core sold separately.

Fasteners:

Four (4) each 5/16" - 18 x 5/8" FHPMS (top bracket)

Two (2) each 5/16" - 18 x 1-1/2" FHPMS (top bracket)

Four (4) each 5/16" - 18 x 1-1/4" FHMS (bottom bracket)

Four (4) each 5/16" - 18 masonry anchors (bottom bracket)

Two (2) each 1/4" - 20 x 1-1/4" FHPMS (top fitting)

Two (2) each 1/4" - 20 thru bolts (top fitting)

Two (2) #10 - 24 x 3/8" - 20 x 1-1/4" FHPMS (top fitting)

Finishes:

USP - grey primer only.

Material:

11 gauge steel tube

Mullion:

2" x 3" (51 mm x 76 mm) - 11 gauge steel tube

Shims:

Two (2) each 1/2" (13 mm) and 5/8" (16 mm) spacers included (top). Two (2) 3/32" (2.4 mm) shims included (bottom).

Strikes:

Fire rated strike and hook kit, 4912 (4500 Series) or 4916 (4700 Series), must be purchased separately.

Top Fitting:

Latching head allows the mullion to be removed in seconds. Mullion can be locked in place without the use of a key.

Warranty:

One-year