

500/600 :: Deadbolt Lock

GENERAL FEATURES:

Keying: Can be keyed together with other R Series locks

Rekeyable: Easily rekeyable via set screw cylinder release mechanism

ANSI/BHMA: Tested to ANSI/BHMA A156.11 Grade 1 cycle testing. Withstood in excess of 40,000 cycles with no damage. All other requirements of ANSI/BHMA A156.11, no less than Grade 2 performance was attained.

US Patent Nos: 4,899,563; 4,920,774

Body: Zinc die cast lock body

Cylinder: Solid brass pin tumbler cylinder

Barrel diameter: 7/8"

500DR includes: 56-1 bar strike

600DW includes: 12-3 angle strike

Finish: 26D, US4 or 10B

Packaged: Packed 10 per box

KEYING INFORMATION:

Keyway: CCL R1

Stock keying: KD/KA - 5 pin standard

Stock KA#: 4T21579, 4T37526

Masterkeying: 5 pin standard, 6 pin available

Keyblank 5-pin: KBR-5-NP (equivalent to C0106, 1003A)

Keyblank 6-pin: KBR-6-NP (equivalent to L1003A)



500DR
DOOR



600DW
DRAWER

| Item | Function | Finish | Cyl. Length | Type | Keying |
|-------|----------|---------------|-------------|----------|---|
| 500DR | Door | 26D, US4, 10B | 15/16" | Deadbolt | KD, KA 4T21579, 4T37526 Custom Keyed |
| 500DR | Door | 26D, US4 | 1-3/8" | Deadbolt | |

Key-Retaining: Specify item 500KL for left-hand doors and 500KR for right-hand doors.

| Item | Function | Finish | Cyl. Length | Type | Keying |
|-------|----------|---------------|-------------|----------|---|
| 600DW | Drawer | 26D, US4, 10B | 15/16" | Deadbolt | KD, KA 4T21579, 4T37526 Custom Keyed |
| 600DW | Drawer | 26D, US4, 10B | 1-3/8" | Deadbolt | |

Key-Retaining: Specify item 600KI for inverted drawers and 600KV for vertical drawers.

ACCESSORIES: For a complete list, see the accessories section of this catalog.

- > WP21 spacer (3/32" thickness)
- > WP22 spacer (1/4" thickness)
- > WP23 spacer (1/2" thickness)
- > 07S, 12-1, 12-2, 12-4, 56-1 strikes
- > TR1256 trim rings
- > Through-bolt plate ETS2, trim pull ETS2-PL and template ETST2 for through-bolt mount

KEY-RETAINING CHART

