
► 200DW | 200B | 200M Drawer Lock



ANSI/BHMA A156.11 Grade 1 E07041

Woodwork Institute (WI) acknowledged product



200DW

Function: Standard function lock Includes: 2 keys, 12-3 bar strike, and lock mounting screws

200B - Weather Resistant

Function: Weather resistant construction. Suitable for outdoor use in covered areas only. Includes: 2 keys, 12-3 bar strike, and lock mounting screws

Function: MRI locks are made of all non-magnetic materials and components specifically for use in

Includes: 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are non-ferrous/non-magnetic)

200M - MRI Function

MRI medical applications.

200DW

Item	Function	Finish	Cyl. Length	Keying	
200DW	Drawer	26D, US4, 10B, US19	15/16" or 1-3/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004*note Custom keyed	
200DW	Drawer	26D, 10B	1-5/8"		
Key-retaining:		Specify item 200KI for inverted drawers and 200KV for vertical drawers. (BKI and BKV designations are only required for key retaining locks).			
Long bolt:		Specify LB for long bolt installed in lock.			

200B - B Series (Weather Resistant)

Item	Function	Finish	Cyl. Length	Keying	
200B	Drawer	26D, US4, 10B, US19	15/16" or 1-3/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004*note Custom keyed	
200B	Drawer	26D, 10B	1-5/8"		
Key-retaining:		Specify item 200BKI for inverted drawers and 200BKV for vertical drawers. (BKI and BKV designations are only required for key retaining locks).			
Long bolt:		Specify LB for long bolt installed in lock.			

200M - MRI Function (Non-Magnetic)

Item	Function	Finish	Cyl. Length	Keying	
200M	Drawer	26D	15/16", 1-3/8" or 1-5/8"	KD, KA 101,103,107,915 KA 51001,51002,51003,51004*note Custom keyed	
Key-retaining (MRI):		Specify item 200MKI for inverted drawers and 200MKV for vertical drawers. (MKI and MKV designations are only required for key retaining MRI locks).			
Long bolt:		Specify LB for long bolt installed in lock.			

^{*}note KA# 51001, 51002, 51003 and 51004 available in US26D finish only

SPECIFICATIONS

Keying: Can be keyed together with other N Series locks

Rekeyable: Easily rekeyable via set screw cylinder release mechanism

ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1 performance requirements. Equivalent to E07121(100DR) / E07041(200DW).

Standard function: Key removable in locked or unlocked position. Standard function locks are non-handed.

Key-retaining: Key removable in locked position only. Specify handing (KL/KR for doors or KI/KV for drawers) when ordering.

US Patent Nos: 4,899,563; 4,920,774

Body: Zinc die cast

Cylinder: Solid brass, pin tumbler Cylinder length: 15/16", 1-3/8" or 1-5/8"

Barrel diameter: 7/8" Finish: 26D, US4, 10B or US19 Packaged: Packed 10 per box

KEYING INFORMATION

Keyway: N Series (equivalent to National D4291 4-pin or D4292 5-pin system)

Keys: Includes 2 keys per lock Stock keying: KD/KA - 4 pin standard Stock KA#: 101, 103, 107, 915, 51001, 51002,

51003, 51004*note

Masterkeyed: 5 pin standard Grand masterkeyed: Available Keyblank 4-pin: KBN-4-NP (equivalent to NA14, 1069L) Keyblank 5-pin: KBN-5-NP (equivalent to NA12, 1069LA)

Keyblank 5-pin copper plated: KBN-5B (use with 100M/200M MRI locks)

INCLUDED ACCESSORIES

200DW/200B: 2 keys, 12-3 angle strike, and lock mounting screws

200M: 2 keys, 56-1 bar strike, and lock mounting screws (keys, components and materials are nonferrous/non-magnetic)

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Spacers: WP20 (3/16" thick), WP21 (3/32" thick), WP22 (1/4" thick), WP23 (1/2" thick) Strikes: 07S, 12-1, 12-2, 12-3, 12-5, 12-4, 56-1

Trim ring: TR1256

Through-bolt hardware: ETS2 trim plate, ETS2-PL

trim pull and ETST2 template

Long bolt (bolt only): 15-1-35 for use with

200DW/200B/200M locks



