Interchangeable Core

Best Compatible (Small Format)

▶ 720 Cam Lock



For BEST style interchangeable core cylinders



ANSI/BHMA Woodwork Institute A156.11 Grade 1 (WI) acknowledged E07261/E07271 product


MOUNTING CUTOUT 1 5/32" 7/8" 7/8"


produ	ct		
	Body	Cyl. Diameter	Mat. Thickn


Item	Finish	Body	Cyl. Diameter	Mat. Thickness	Description
720LM/DM	26D, US26, US3	Zinc die cast	1-1/8"	Up to 1-1/8"	Lock body - For small format IC

720-PL3


Anti-rotation plate








INCLUDED CAMS



720-3-1 for inverted function



720-3-2 inbent cam for vertical function (bottom-pin style)

SPECIFICATIONS

Retrofits: Best 1E7E4

ANSI/BHMA: Passed ANSI/BHMA A156.11 Grade 1 performance requirements. Equivalent to E07261/

E07271.

Cylinder diameter: 1-1/8" Across flats: 7/8"

Max. material thickness: 1-1/8" Min. material thickness: 0.08"

Functions: Includes parts for key-retaining or

non-key-retaining function

Body: Zinc die cast or machined solid brass

Finish: 26D, US26, US3 or US4 **Packaged:** Packed 10 per box

KEYING INFORMATION

Cores: Not included.

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen XT or VIDEX CyberLock SFIC cylinders

INCLUDES

725-PA plastic thumbturn
720-PL3 stabilizer plate
725-1 spacer to fit 6 or 7 pin cores
720-3-1 short inverted cam
720-3-2 long vertical cam
720-CDLM lost motion cam shifter
720-CDDM key retaining door cam shifter
720-KR key retaining drawer cam shifter

OPTIONAL ACCESSORIES

See accessories on page 76-77. See page 77 for cam assembly instructions.

Optional cams: 720-3-3, 720-3-4, 720-3-5

Trim collars: TR200 Series
Switch accessory pack: SW-1

CL-MP-118: Double-D metal punch (page 66) SFIC cores: 206/207 Series (page 60)