► PA Series Plastic Thumbturns

1

FOR INTERCHANGEABLE CORE LOCKS

Item	Description				
725-PA	Ships standard with small format IC locks: L72V,720,721,722,724,725, 728,729,950 locks				
	Ships standard with Corbin/Russwin IC locks: CR1125,CR25				
7788-PA-D	Ships standard with Schlage FSIC locks: L92V,777,888,920,929				
931-PA	Ships standard with Medeco/Yale IC locks: 931,ME93,YA93				

SPECIFICATIONS

Description: Black or gray plastic thumbturn **Purpose**: Operate lock without core

Material: Plastic

▶ **78-201** Schlage C Keyway Cylinders



cylinder



CYLINDER ORDERING GUIDELINES

Item No.	Finish	Universal Driver 10-360 Position		For use with	Keying
78-201H26D-CUST 78-201HUS4-CUST	26D US4	Horizontal	Ô	700LC 829R-LC 850S	KA, KD or MK
78-201V26D-CUST 78-201VUS4-CUST	26D US4	Vertical	O	800LC 820LC	KA, KD or MK
78-201-26D-CUST 78-201-US4-CUST	26D US4	N/A	10-360 driver not required	L78	KA, KD or MK

SPECIFICATIONS

Cylinder: Solid brass, drilled for 6 pins Finish: US26D or US4 finish

Keyway: Schlage C

Keying: Specify keying at time of order

Use: Works with Olympus less cylinder (for Schlage

standard cylinder) cabinet locks

Universal driver: Position of the 10-360 universal driver in the back of the cylinder is dependent on the specific lock the cylinder will be used in. Please see ordering information below.

Cylinder includes: 2 operating keys and 10-360 universal driver, and 1 each 10-361 (1-1/8) and 10-362 (1-3/8) tailpiece/driver bar.

ORDERING INFORMATION

Orientation of universal driver (p/n 10-360) in back of cylinder is based on the Olympus item the cylinder will be used with. See the **For use with** section of the chart opposite for ordering information and cylinder part-numbers.

OTHER ACCESSORIES

Keys: For additional keys see page 55

