▶ **820** Cam Lock



Woodwork Institute (WI) acknowledged product







anti-rotation plate

Item	Finish	Cyl. Diameter	Mat. Thickness	Keying
820S	26D, US3	1-1/8"	Up to 1-3/8"	KD, KA 101, 102, 0-Bit Custom Keyed
820LC	26D. US3	1-1/8"	Up to 1-3/8"	Less Cylinder


MOUNTING CUTOUT








INCLUDED CAMS



720-3-1 for inverted function



720-3-2 inbent cam for vertical function (bottom-pin style)

SPECIFICATIONS

Rekeyable: Easily rekeyable via set screw on back

of lock body

U.S. Patent No: 7,716,958 B2 Cylinder diameter: 1-1/8" Across flats: 7/8"

Max. material thickness: 1-3/8" Min. material thickness: 0.08"

Body: Zinc die cast

Functions: Includes parts for key-retaining or non-

key-retaining Finish: 26D or US3

Packaged: Packed 10 per box

820S KEYING INFORMATION

Keying: Can be keyed together with other Schlage

C Keyway locks

Keyway: Schlage "C" Keyway Keys: Includes 2 keys per lock Cylinder: Solid brass, pin tumbler Stock keying: KD/KA - 5 pin standard Stock KA#: 101, 102, O-Bit Masterkeying: 6 pin standard

Masterkeying: 6 pin standard Grand masterkeying: Available Keyblank 6-pin: KBSC-6

820LC CYLINDER INFORMATION

Cylinder: Not included

Accepts: Schlage compatible key-in-knob cylinders including ILCO cylinder #1599. This lock does not

accept Medeco cylinders.

 Includes: All parts necessary to work with other manufacturers' Schlage compatible cylinders.
 Compatible electronic cylinders: ASSA CLIQ or VIDEX CyberLock key-in-knob cylinders.

INCLUDED ACCESSORIES

720-PL3 anti-rotation plate
720-3-1 short inverted cam
720-3-2 long vertical cam
720-CDLM lost motion cam shifter
720-CDDM key retaining door cam shifter
720-KR key retaining drawer cam shifter

OPTIONAL ACCESSORIES

See accessories on page 76-77. See page 77 for cam

assembly instructions.

Optional cams: 720-3-3, 720-3-4, 720-3-5

Trim collars: TR200 Series Cylinder: 78-201 Series (page 61) Switch accessory pack: SW-1

CL-MP-118: Double-D metal punch (page 66)