▶ 829R Showcase/Ratchet Lock



For SCHLAGE style original or replacement cylinders

Less cylinder

locks


(WI) acknowledged

product


FOR BYPASSING SLIDING DOORS

TOR DITASSING SCIDING DOORS			
Item	Finish	Mat. Thickness	Keying
829R	26D	Up to 1/4"	KD, KA 101, 102, O-Bit Custom Keyed
829R-LC	26D	Up to 1/4"	Less Cylinder
829-MD	Medeco Driver Pack (required if installing Medeco cylinders in LC (less cylinder product). Sold separately.		
Optional straps:	729RS-2 fits up to 3/8" material thickness 729RS-3 fits up to 5/8" material thickness (adjustable)		

^{*}Standard and optional straps with nylon coating available August 2019



OPTIONAL STRAPS



SPECIFICATIONS

Rekeyable: Easily rekeyable via set screw cylinder

release mechanism

ANSI/BHMA: Complies with clause 6.3 (8.2~8.4) of

ANSI/BHMA A156.11 ANSI standards **Use:** Sliding glass or wood doors

Body: Zinc die cast Strap: Steel

Finish: 26D

Packaged: Packed 10 per box

829R KEYING INFORMATION

Keying: Can be keyed together with other Schlage

C Keyway locks

Keyway: Schlage C keyway Keys: Includes 2 keys per lock Cylinder: Solid brass pin, tumbler Stock keying: KD/KA - 5 pin standard Stock KA#: 101, 102, O-Bit

Masterkeying: 6 pin standard Grand masterkeying: Available Keyblank 6-pin: KBSC-6

829R-LC CYLINDER INFORMATION

Cvlinder: Not included

Includes: All parts necessary to work with other

manufacturers' cylinders

Accepts: Schlage compatible key-in-knob cylinders including ILCO cylinder #1599 and Medeco

cylinders

Medeco cylinders: Requires optional 829-MD Medeco Driver Pack (available separately.) Will accept the following Medeco cylinders:

Original: 6 pin #20-00954 5 pin #20-00854 Biaxial: 6 pin #20W00954 5 pin #20W00854 Keymark: 6 pin #20K00954 Key retaining cylinder: #20W20051

Compatible electronic cylinders: Medeco LOGIC, ASSA CLIQ or VIDEX CyberLock key-in-knob cylinders

INCLUDES

729RS-1 strap for 3/16" to 1/4" material thickness

OPTIONAL ACCESSORIES

Alternate straps: 729RS-2 strap for 3/8" material thickness, or 729RS-3 strap for up to 5/8" material thickness

Medeco driver pack: 829-MD (required if using

Medeco cylinders)

Cylinder: 78-201 Series (page 61)

