Interchangeable Core


► L72V Latch Lock



For BEST style interchangeable core cylinders



For door applications, place lock on side.






Left-Hand Door

Right-Hand Door

Item	Handing	Finish	Cyl. length	Keying
L72V	VH Drawer	26D, US3	1-1/4"	Lock body - For small format IC
L72V-SP1	VH Drawer	26D, US3	1-1/4"	Lock body - For Sargent XC or Marks high security cores with side pins. Includes short pin prong driver no. L72V-PD-SP1.



SPECIFICATIONS

Function: Spring latch Body: Zinc die cast Barrel diameter: 1-1/8" Cylinder length: 1-1/4" Latch projection: 3/8" Finish: 26D or US3

Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen

Best Compatible (Small Format)

XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

10-350 spacers (qty 3) L78ST-1-SS matching lip strike 725-1 spacer to fit 6 or 7 pin cores 725-PA plastic thumbturn

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Prong drivers: Shortened prong driver for use with Sargent XC or Marks high security cores with side pins. Specify L72V-PD-SP1 (for prong driver only). Spacers: 10-350 (1/8" thick), 10-348 (1/4" thick),

10-349 (1/2" thick) **Trim ring:** TR78

Through-bolt hardware: ETS1 trim plate, ETS1-PL

trim pull and ETST1 template
SFIC cores: 206/207 Series (page 60)


▶ 950 Deadlatching Lock



For BEST style interchangeable core cylinders



Item	Handing	Finish	Cyl. length	Description
950IC	VH Drawer	26D, US3	1-1/8"	Lock body - For small format IC



SPECIFICATIONS

Function: Deadlocking latch

U.S. Patent No: 4,899,563; 4,922,774; 5,657,652

Body: Zinc die cast Cylinder length: 1-1/8" Barrel diameter: 1-1/8" Latch projection: 1/4" Finish: 26D or US3

Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included.

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen

XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

10-350 spacers (qty 2) 725-1 spacer to fit 6 or 7 pin cores 850-210 matching strike 725-PA plastic thumbturn

OPTIONAL ACCESSORIES

See the accessories section of this catalog for a complete list.

Spacers: 10-350 (1/8" thick), 10-348 (1/4" thick),

10-349 (1/2" thick) **Trim ring:** TR78

Through-bolt hardware: ETS1 trim plate, ETS1-PL

trim pull and ETST1 template
SFIC cores: 206/207 Series (page 60)

