

The global leader in  
door opening solutions

## Rockwood 2940 - Automatic Flush Bolt, Top Bolt Only



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

SIZE:  
1" x 8 1/2"

WEIGHT:  
1.5 lbs.

ANSI A156.3:  
Type 25

### Specifications:

#### MATERIAL:

Brass, Stainless Steel

#### FASTENERS:

6 ea. #8 x 3/4" Flat Head Combo Screws; 2 ea. #8-32 x 1/2" Flat Head Machine Screws  
3 ea. #10 x 1" Flat Head Wood Screws; Note: No plastic anchor required for top only

#### FEATURES:

- For wood doors
- Non-handed
- Fully automatic—opening active door retracts top and bottom bolts
- Low closing force
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes
- Bolt head rods are adjustable up to 1/2"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- UL Listed



300 Main Street  
Rockwood, Pennsylvania 15557  
P: 800.458.2424 • F: 800.922.9212  
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.