

The global leader in  
door opening solutions

## Rockwood 2962 - Automatic Flush Bolt Set



### Specifications:

#### MATERIAL:

Brass, Stainless Steel

#### FASTENERS:

8 ea. #8 x 1" Flat Head Sheet Metal Screws,  
8 ea. #8 x 3/4" Flat Head Combo Screws,  
4 ea. Plastic Anchors

#### FEATURES:

- Patent #7,410,195
- Durable, tested over 1 million cycles
- Smaller profile adds stability to the door
- Only two 1 1/8" diameter holes for easier door preparation
- Preparation prevents the veneer from splitting at the corners of the door
- Quiet & smooth activation
- Fully automatic; opening active door retracts top & bottom bolts
- Non-handed
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Low (3 lbs. maximum) closing force. ADA Compliant.
- Adjustable Bolt Head Rods: bolts can be vertically adjusted 1/2" for unusual clearances
- For up to 4'w x 9'h fire rated wood core & composite doors up to 1 1/2 hours fire rating
- UL Listed



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

#### FACE PLATE SIZE:

1 1/8" x 2 1/4"

#### WEIGHT:

1.7 lbs.