

## Rockwood 555 x 18BFB - Lever Extension Flush Bolt with Bottom Fire Bolt



### Available Finishes:

- US26D/626

### SIZE:

Top Bolt: 1" x 6 <sup>3</sup>/<sub>4</sub>"  
Bottom Bolt: Ø <sup>13</sup>/<sub>16</sub>"

### WEIGHT:

0.9 lbs.

### Specifications:

#### MATERIAL:

- Flush Bolt - Brass
- Bottom Fire Bolt - Stainless Steel

#### FASTENERS:

8 ea. #8 x <sup>3</sup>/<sub>4</sub>" Flat Head Combo Screws

#### FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 9'h rated up to and including 3 Hours
- Fits ANSI A115 door and frame preparation
- <sup>3</sup>/<sub>4</sub>" bolt throw, <sup>3</sup>/<sub>4</sub>" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 <sup>1</sup>/<sub>2</sub>" adjustable bolt head
- When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment

#### OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Extra long bolt head - 2 <sup>1</sup>/<sub>2</sub>" (or to your specification)

