

The global leader in
door opening solutions

Rockwood 2949 - Self Latching Flush Bolt with Bottom Fire Bolt for Fire Rated Wood Doors



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

SIZE:

Top Bolt: 1" x 8 1/2"

Bottom Bolt: Ø 13/16"

WEIGHT:

1.6 lbs.

Specifications:

MATERIAL:

Brass, Stainless Steel

FASTENERS:

6 ea. #8 x 3/4" Flat Head Combo Screws, 2 ea. Plastic Anchors; 3 ea. #10 x 1" Flat Head Wood Screws

FEATURES:

- Non-handed
- Low (5 lbs. maximum) closing force
- Self latching top bolt
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 1 1/2"
- For fire rated UL listed 20-minute wood core and composite doors up to 4'w x 9'h
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment



300 Main Street

Rockwood, Pennsylvania 15557

P: 800.458.2424 • F: 800.922.9212

www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.