

Architectural Door Accessories

ASSA ABLOY

The global leader in
door opening solutions

Rockwood OH103H - Heavy Duty Concealed - Hold Open Center Hung 36 1/16" - 41"



Specifications:

MATERIAL:
Stainless Steel

FASTENERS:
Jamb: 1/4"-20 x 3/4" Flat Head Machine Screws or #14 x 1 1/2" Flat Head Wood Screws
Door: 5/16"-18 x 1 1/2" Flat Head Machine Screws or #18 x 3" Flat Head Wood Screws

FEATURES:

- Doors may be single or double acting
- Non-handed
- Slide track design
- Recommended for high traffic, heavy abuse installations
- Heavy shock absorber spring provides 5-7° compression before deadstop
- Surface on/off knob on hold open models
- Complete screw packet for installation in wood and machine screws for door and frame
- For security areas, Torx® screws available for exposed fasteners
- Durable slider cam and shock block
- 110° maximum opening
- 1 3/4" minimum door thickness, for thicker doors, note thickness when ordering
- 1 3/16" square channel
- Stop function UL listed for fire door assemblies

OPTIONS:

- Hold Open
- Butts/Offset Pivots 33 1/16" - 38"



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US32/629
- US32D/630

WEIGHT:
4.5 lbs.

ANSI A156.8:
C01511

300 Main Street
Rockwood, Pennsylvania 15557
P: 800.458.2424 • F: 800.922.9212
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.

CS-OH103H 1/17