

The global leader in  
door opening solutions

## Rockwood OH1002M - Standard Duty Surface Mounted - Multi-Function - Center Hung 26 <sup>9</sup>/<sub>16</sub>" - 32"



### Specifications:

**MATERIAL:**  
Stainless Steel

**FASTENERS:**  
Jamb: #12 x 1 <sup>1</sup>/<sub>2</sub>" Flat Head Wood Screws or #12-24 x <sup>1</sup>/<sub>2</sub>" Flat Head Machine Screws  
Door: #12-24 x 1 <sup>1</sup>/<sub>2</sub>" Flat Head Machine Screws and Ø <sup>5</sup>/<sub>16</sub>" Sex Bolt

**FEATURES:**

- Single acting doors
- Non-handed
- Slide track design
- Recommended for medium traffic, medium weight doors
- Degree of opening fully adjustable and can be adapted to changing needs
- Heavy shock absorber spring provides compression before deadstop
- Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in field. MF5012 KIT (Adapter kit) included.
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications
- Durable slider cam and shock block
- 110° maximum opening
- <sup>3</sup>/<sub>4</sub>" square channel
- Stop function UL listed for fire door assemblies
- For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000

**OPTIONS:**

- Multi-function
- Butts/Offset Pivots 24 <sup>1</sup>/<sub>16</sub>" - 30"
- Multi-function unit can be converted to a hold open or friction unit in the field

### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US32/629
- US32D/630

**WEIGHT:**  
3.5 lbs.

