

The global leader in
door opening solutions

Rockwood OH1003M - Standard Duty Surface Mounted - Multi-Function - Center Hung 32 1/16" - 38"



Specifications:

MATERIAL:

Stainless Steel

FASTENERS:

Jamb: #12 x 1 1/2" Flat Head Wood Screws or #12-24 x 1/2" Flat Head Machine Screws

Door: #12-24 x 1 1/2" Flat Head Machine Screws and Ø 5/16" Sex Bolt

FEATURES:

- Single acting doors
- Non-handed
- Slide track design
- Recommended for medium traffic, medium weight doors
- Degree of opening fully adjustable and can be adapted to changing needs
- Heavy shock absorber spring provides compression before deadstop
- Multi-function unit is shipped as a stop. Can be converted to a hold opener friction in field. MF5012 KIT (Adapter kit) included.
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications
- Durable slider cam and shock block
- 110° maximum opening
- 3/4" square channel
- Stop function UL listed for fire door assemblies
- For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000

OPTIONS:

- Multi-function
- Butts/Offset Pivots 30 1/16" - 36"
- Multi-function unit can be converted to a hold open or friction unit in the field

Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US32/629
- US32D/630

WEIGHT:
3.5 lbs.

