

## Rockwood OH202M - Standard Duty Concealed - Multi-Function - Center Hung 27" - 32"



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US32/629
- US32D/630

WEIGHT:  
3.5 lbs.

### Specifications:

#### MATERIAL:

Stainless Steel

#### FASTENERS:

Jamb: #12-24 x 1/2" Flat Head Machine Screws or #12 x 1 1/2" Flat Head Wood Screws

Door: #12-24 x 1 1/2" Flat Head Machine Screws or #12 x 1 1/2" Flat Head Wood Screws

#### FEATURES:

- Doors may be single or double acting
- Non-handed
- Slide track design
- Recommended for medium traffic, medium weight doors
- Degree of opening is fully adjustable and can be adapted to changing needs
- Heavy shock absorber spring provides 5-7° compression before deadstop
- Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in the field. MF5012 KIT (Adapter kit) included
- Complete screw packet kit for installation in wood or metal door and frame
- For security areas, Torx® screws available for exposed fasteners, but heavy-duty units should be considered for high security applications
- Durable slider cam and shock block
- 110° maximum opening
- 3/4" square channel
- Stop function UL listed for fire door assemblies



#### OPTIONS:

- Multi-function
- Butts/Offset Pivots 24 1/16" - 30"