

The global leader in
door opening solutions

Rockwood OH904S - Heavy Duty Surface Mounted - Stop Only Center Hung 41 1/16" - 46"



Specifications:

MATERIAL:

Stainless Steel

FASTENERS:

Jamb: 1/4"-20 x 3/4" Flat Head Machine Screws or #14 x 1 1/2" Flat Head Wood Screws

Door: 5/16"-18 x 2" Flat Head Machine Screws and 1/2" dia. Sex Bolt

FEATURES:

- Doors are single acting
- Non-handed
- Slide track design
- Recommended for high traffic, heavy abuse installations
- Heavy shock absorber spring provides 5-7° compression before dead stop
- On/off knob on hold open models
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications
- Durable slider cam and shock block
- 110° maximum opening
- 1 3/4" minimum door thickness
- 1 3/16" square channel
- Stop function UL listed for fire door assemblies
- For pull side mounting or flush mounting on push side or for rabbeted push side use angle jamb bracket adapter JB900LH or JB900RH

OPTIONS:

- Stop Only
- Butts/Offset Pivots 38 1/16" - 43"

Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US32/629
- US32D/630

WEIGHT:

4.5 lbs.

ANSI A156.8:

C02541



300 Main Street

Rockwood, Pennsylvania 15557

P: 800.458.2424 • F: 800.922.9212

www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.