

## Rockwood 301 - Mortise Door Edge



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US32D/630
- US32DMS
- US32D316

ANSI 156.6: J205

### Specifications:

#### MATERIAL:

.050" Brass, Bronze, Prime Coated Steel, Stainless Steel

#### FASTENER:

#6 x <sup>5</sup>/<sub>8</sub>" Flat Head Sheet Metal Screws

#### ORDERING:

- Specify any length up to 96" (standard lengths are 42", 84", 96")

*NOTE: 84" and 96" are made to match net door height – specify*

#### FEATURES:

- Door edges are sized to be mortised into the surface of 1<sup>3</sup>/<sub>4</sub>" thick wood doors (advise if your door is another thickness)

*NOTE: Some wood doors that are nominally 1<sup>3</sup>/<sub>4</sub>" vary significantly*

#### OPTIONS:

- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1<sup>1</sup>/<sub>2</sub>" hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (300-UL)
- Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)