

The global leader in  
door opening solutions

## Rockwood 306B - Non-Mortise Door Edge



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US32D/630
- US32DMS
- US32D316

### Specifications:

#### MATERIAL:

.050" Brass, Bronze, Prime Coated Steel, Stainless Steel

#### FASTENER:

#6 x  $\frac{5}{8}$ " Flat Head Sheet Metal Screws

#### ORDERING:

- Specify any length up to 96" (standard lengths are 42", 84", 96")
- NOTE: 84" and 96" are made to match net door height – specify*
- Specify wood or metal door

#### FEATURES:

- Door Edges are sized for 1  $\frac{3}{4}$ " thick wood or metal doors (advise if your door is another thickness)
- NOTE: Some wood doors that are nominally 1  $\frac{3}{4}$ " vary significantly*

#### OPTIONS:

- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1  $\frac{1}{2}$ " hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (306B-UL)
- Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)

300 Main Street  
Rockwood, Pennsylvania 15557  
P: 800.458.2424 • F: 800.922.9212  
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.