# Architectural Door Accessories



Experience a safer and more open world

## Rockwood 309 - Overlapping Door Edges



Available Finishes:	
<ul> <li>US3/605</li> <li>US4/606</li> <li>US10/612</li> <li>US10B/613</li> <li>US10BE/613E</li> <li>US32D/630</li> <li>US32DMS</li> <li>US32D316</li> </ul>	
ANSI 156.6: J202	

## **Specifications:**

### MATERIAL:

.050" Brass, Bronze, Stainless Steel

FASTENER: #6 x <sup>5</sup>/s" Flat Head Sheet Metal Screws

ORDERING: Specify any length (standard length is 42"). Specify wood or metal door

### **OPTIONS:**

- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1 1/2" hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (309-UL)
- Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

