## Architectural Door Accessories



The global leader in door opening solutions

Specifications:         Muminum, Brass, Bronze, or Stainless Steel	<ul> <li>Finishes:</li> <li>US3/605</li> <li>US4/606</li> <li>US10/612</li> <li>US10B/613</li> <li>US10BE/613E</li> <li>US26/625</li> <li>US26D/626</li> <li>US22629</li> <li>US32316</li> <li>US32D/630</li> <li>US32D316</li> <li>US32DMS</li> <li>313/710</li> <li>314</li> <li>315/711</li> </ul>
- MATERIAL: Aluminum, Brass, Bronze, or Stainless Steel	
Aluminum, Brass, Bronze, or Stainless Steel	Powder Coat
MOUNTINGS:	SIZE: Ø 1"
<ul> <li>Metal and Wood: T3 Back to Back and Thru Bolt; Pull Free End = 1, Push Free End = 1, Common End = 5</li> <li>Metal: T4 Back to Back and Concealed; Pull Free End = 6, Push Free End = 6, Common End = 5</li> <li>Wood: T5 Back to Back and Concealed; Pull Free End = 8, Push Free End = 8, Common End = 5</li> <li>Metal &amp; Wood: T1 Back to Back and Decorative Bolt; Pull Free End = 12, Push Free End = 12, Common End = 5</li> <li>Glass: T2 Back to Back and Thru Bolt; Pull Free End = 15, Push Free End = 15; Common End = 13</li> <li>T3 is the standard mounting method for Metal and Wood Doors. (See mounting selections at rockwoodmfg.com)</li> </ul>	CTC: Pull 18" PROJECTION: Pull 3 <sup>1</sup> /2" Push 2 <sup>3</sup> /4"
ORDERING: Specify product number, mounting, door type, push bar CTC, and finish (i.e., BF15947 T3, wood door, 33" CTC, US32D316)	CLEARANCE: Pull 2 1/2" Push 1 3/4"
OPTIONS: • Engraving "PUSH" or "PULL" (specify handing) • Base plates available — use BP prefix (BPBF15947) when ordering • Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF15947 T3HD)	WEIGHT: 15.0 lbs. ANSI 156.6: J505

Rockwood, Pennsylvania 15557 P: 800.458.2424 • F: 800.922.9212 www.rockwoodmfg.com • orders.rockwood@assaabloy.com