

ASSA ABLOY

The global leader in
door opening solutions

Technical drawings of the UL 1000 Series Fire-Resisting Door Hardware, showing front, side, and detail views with dimensions.

Front View (Left): Shows the door plate with a 2" width and 1" height. Dimensions include 1/4" and 5/8" for the top section, and 1/2" for the bottom section. A 3/4" dimension is shown for the top section.

Side View (Right): Shows the door plate with a 2 1/4" width and 15/16" height. Dimensions include 5/64" for the top section, 15/8" for the bottom section, and 1 1/2" for the total height. A 3/4" dimension is shown for the top section.

Detail View (Bottom): Shows the door plate with a 1 3/8" width and 6 3/4" height. Dimensions include 1/8" for the top section, 3 3/8" for the bottom section, and 1/4" for the bottom section. A 1/2" dimension is shown for the bottom section. The text "(two) #8x1 Combo" is present.

UL Logo: The UL logo is located in the bottom left corner.

Labels: The labels "STRIKE", "Mortise", and "Face Plate Mortise" are present. The text "dp. 1/8" x 1" x 6 3/4" Face Plate Mortise" is also present.

NOTE: ASSA ABLOY reserves the right to make product changes and is not responsible for obsolete template errors. To ensure your template is current, please visit our website at www.assaabloydooraccessories.us or call us at 800-458-2424.

Diagram illustrating the installation of the Plug and 18BFB into the Active and Inactive Doors. The Active Door has a $\text{Ø } 13/32''$ Hole and a height of 6". The Inactive Door has a $\text{Ø } 9/16''$ Hole and a height of 6". The Plug is shown being inserted into the Active Door, and the 18BFB is shown being inserted into the Inactive Door.

IMPORTANT: The 18BFB will project during a fire. Do not cover with any edge mounted door hardware.