## Architectural Door Accessories



## Rockwood 310BS Non-Mortised Lock Side Overlapping Door Edge Order Form

Experience a safer and more open world

Company Name:		Date:			
Account #:					
		PO#:			
Order Line #:	Quantity:	Handing:	Tag. No's:		
Finish:	_	310BS:			
Select Cutout, Door Type and Fill in Dimensions:	□ 161 Latch	s" □ Metal	Door	□ Wood Doo	
□ UL Rated	□ 86 Mortise Lock		- <del>-</del>		
*Door Edge Height if different from net door height	□ ASA Strike □ ASA Strike	4"	·		
Specify Mounting (if not standard)	□ Cylindrical → 11/23/	g" 			
Torx Screws     Tek Screws	☐ Manual/ Automatic Flush Bolt (Metal Door)				
* Standard Door Thickness is 1 <sup>3</sup> / <sub>4</sub> " if not please advise:  * Standard Leg Length	□ Manual Flush Bolt (Wood Door)	(Net Door Height) *84" and 96" are opening			
for non-mortised edge is 1 1/4" if not please advise:	□ Automatic Flush Bolt (Wood Door)	sizes - please provide net door height.	*84" and 96 sizes - p	oor Height) "are opening lease provide t door height.	
Note: Your door thickness is a nominal dimension. Doors can vary + or – 1/16* from the nominal dimension. When ordering, verify actual door thickness to assure a working	Fire Bolt  Active   Office   Door   G"   Door				

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature) (date)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Canada:
Door Security Solutions Canada
160 Four Valley Drive
Vaughan, ON L4K 4T9
P: 800.461.3007
www.assaabloydss.ca