Architectural Door Accessories



Rockwood 302 Mortised Lock Side Door Edge Order Form

Experience a safer and more open world

Customer Information Company Name: Account #:		Phone/Fax:	
			Tag. No's:
Finish:	_	302:	
Select Cutout, Door Type and Fill in Dimensions:	□ 161 Latch Bolt □ 161 Latch □ 2 1/4" □ 1/4"	□ Metal Door	□ Wood Door
□ UL Rated	□ 86 Mortise		
Door Edge Height if different from net door height	$\square \text{ ASA Strike} \qquad \square \bigcap_{\substack{i=1\\i=1\\4^{7}/s^{}}}^{\square \bigcap_{i=1}^{1-1}}$		
Specify Mounting (if not standard)	□ Cylindrical ☐ 1 1/8" Strike ☐ 2 3/4"		
 Torx Screws * Standard Door Thickness is 1 ³/₄" if not please advise: 	□ Manual/ Automatic Flush Bolt (Metal Door) □ Manual Flush Bolt	(Net Door Height)	
* Standard Leg Length for mortised edge is ⁷ /s" if not please advise:	(Wood Door) $\begin{bmatrix} 6^{3/4} \\ 6^{3/4} \end{bmatrix}$ Automatic Flush Bolt (Wood Door) $\begin{bmatrix} 8^{1/2} \\ 8 \end{bmatrix}$	*84" and 96" are opening sizes - please provide net door height.	(Net Door Height) * 84" and 96" are opening sizes - please provide net door height.
Note: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.	Fire Bolt Active 01 1 1 1 1 1 1 1 1	6"	of a prep location on the edge of the door.

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature) (date)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Canada:
Door Security Solutions Canada
160 Four Valley Drive
Vaughan, ON L4K 4T9
P: 800.461.3007
www.assaabloydss.ca