Architectural **Door Accessories**



Rockwood 305 Non-Mortised Lock Side Door Edge Order Form

Experience a safer and more open world

Fill out this form and email	to: orders.rockwood@assaabl	oy.com / or fax to: 800-	922-9212	
Customer Information				
Company Name:		Date:		
Account #:			/	
	PO #:			
Order Line #:	Quantity:	Handing:		Tag. No's:
Finish:				
Select Cutout, Door Type and Fill in Dimensions:	$\square 161 Latch \\ Bolt \\ \square 1/4"$	□ Me	tal Door	□ Wood Door
UL Rated	□ 86 Mortise			
*Door Edge Height if different from net door height	$\Box \text{ ASA Strike } \qquad $			
Specify Mounting (if not standard)	□ Cylindrical Strike			
Torx ScrewsTek Screws	□ Manual/ Automatic Flush Bolt		,	
* Standard Door Thickness is 1 ³ /4" if not please advise:	(Metal Door) □ Manual Flush Bolt (Wood Door)	(Net Door Height) *84" and 96" are opening		
* Standard Leg Length for non-mortised edge is 1 '/4" if not please advise:	□ Automatic Flush Bolt (Wood Door)	sizes - please provide net door height.		(Net Door Height) * 84" and 96" are opening sizes - please provide net door height.
Note: Your door thickness is a nominal dimension. Doors can vary $+$ or $-1/16^{\circ}$ from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.	Fire Bolt □ Active ^{of} □ Inactive Door 6" Door	6" 	-	of a prep location on the edge of the door.

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Canada: Door Security Solutions Canada 160 Four Valley Drive Vaughan, ON L4K 4T9 P: 800.461.3007 www.assaabloydss.ca

(date)