Architectural Door Accessories



Rockwood 306-AST Non-Mortised Lock Side Door Edge Order Form

Experience a safer and more open world

Customer Information Company Name: Account #:		Phone/Fax:	!
Order Line #:	Quantity:	Handing:	Tag. No's:
Finish:	_	306-AST:	
Select Cutout, Door Type and Fill in Dimensions:	□ 161 Latch Bolt □ 161 Latch □ 2 1/4" □ 1 1/4"	□ Metal Door	□ Wood Door
□ UL Rated*Door Edge Height if different	□ 86 Mortise 8" 8" Lock		
from net door height Astragal Side Active Door Inactive Door	□ ASA Strike □ Cylindrical Strike □ Cylindrical		
Specify Mounting (if not standard) • Torx Screws • Tek Screws	□ Manual/ Automatic Flush Bolt (Metal Door)		
* Standard Door Thickness is 1 ³ / ₄ " if not please advise:	□ Manual Flush Bolt (Wood Door)	(Net Door Height) *84" and 96" are opening sizes - please provide	
* Standard Leg Length for non-mortised edge is 1 ¹ / ₄ " if not please advise:	□ Automatic Flush Bolt (Wood Door)	net door height.	(Net Door Height) * 84" and 96" are opening sizes - please provide net door height.
Note: Your door thickness is a nominal dimension. Doors can vary + or - 1/16° from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.	Fire Bolt Active Officer Door G" Door Door	6"	or of a prep location on the edge of the door.

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature) (date)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Canada:
Door Security Solutions Canada
160 Four Valley Drive
Vaughan, ON L4K 4T9
P: 800.461.3007
www.assaabloydss.ca