Architectural **Door Accessories**



Rockwood 306B Non-Mortised Lock Side Door Edge Order Form

Experience a safer and more open world

Fill out this form and email	to: orders.rockwood@assaab	loy.com / or fax to: 800-92	22-9212		
Customer Information					
Company Name:					
Account #:	Phone/Fax:	:	//		
		PO #:			
Order Line #:	Quantity:	Handing:		Tag. No's:	
Finish:	-	306В:			
Select Cutout, Door Type and Fill in Dimensions:	$\square 161 \text{ Latch} \qquad 1000000000000000000000000000000000000$	□ Meta	al Door	I	□ Wood Door
UL Rated	B6 Mortise				
*Door Edge Height if different from net door height	$\Box \text{ ASA Strike} \qquad \qquad$				
Specify Mounting (if not standard)	□ Cylindrical Strike	*			
Torx ScrewsTek Screws	□ Manual/ → '→ '→ 1" Automatic Flush Bolt				
* Standard Door Thickness is 1³/4" if not please advise:	(Metal Door) □□* □ Manual Flush Bolt (Wood Door) □ 6 ^{3/4"}	(Net Door Height) * 84" and 96" are opening			_]_ [
* Standard Leg Length for non-mortised edge is 1 ¹ /4" if not please advise:	□ Automatic Flush Bolt (Wood Door)	sizes - please provide net door height.		(Net Door Height *84" and 96" are openin sizes - please provid net door heigh	g
Note: Your door thickness is a nominal dimension. Doors can vary $+$ or $-1/16^{\circ}$ from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.	Fire Bolt - Active of the boor Door of the boor 		esentation of	a prep location on the e	

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Copyright © 2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole

Canada: Door Security Solutions Canada 160 Four Valley Drive Vaughan, ON L4K 4T9 P: 800.461.3007 www.assaabloydss.ca

(date)