Rockwood 308

ASSA ARI OY

ROCKWOOD

Door Edge

Overlapping Non-Mortised Lock Side

Experience a safer and more open world

Company Name:		Date:		
Account #:		Phone/Fax:		<i></i>
Email:		PO #:		
Order Line #:	Quantity:	Handing:	Tag. No's:	
inish:		308:		
Select Cutout, Door Type and Fill in Dimensions:	□ 161 Latch Bolt □ 161 Latch □ 1/8" □ 2/4" □ 1/4"	□ Met	ral Door	□ Wood Doo
UL RatedDouble Egress Doors	□ 86 Mortise Lock			
*Door Edge Height if different from net door height	□ ASA Strike			
Specify Mounting (if not standard) • Torx Screws • Tek Screws	Strike \[\frac{1}{2}^{3/4"} \] \[Manual/ \] Automatic \[Flush Bolt \] \[\begin{array}{cccccccccccccccccccccccccccccccccccc			
* Standard Door Thickness is 1³/₄" if not please advise: * Standard Leg Length	04 15 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	(Net Door Height) *84" and 96" are opening sizes - please provide		
for non-mortised edge is 11/4" if not please advise:	□ Automatic Flush Bolt (Wood Door)	net door height.	*84" and 9	Door Height) 6" are opening blease provide et door height.
a nominal dimension. Doors can vary + or $-\frac{1}{16}$ " from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.	Fire Bolt Active Door Door Door	6"	esentation of a prep loa	tation on the edge of the doc

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424