Rockwood RM7511

Knurled Series

Offset Pull – Flat Ends



Experience a safer and more open world

Complete this form	and email to:	orders.rockwood	@assaablo	y.com / or fax	x to: 800.922.	9212	
Customer Informa	ıtion						
Company Name: _	Date:						
Account #:	Phone/Fo			/			
Email:				PO #:		_ Line #: _	
Quantity:					- <u>-</u>	\neg	
Note – Finish Opt Split Finishes will be the sa	(2	ection 3/4"		Typical Center of Post to End of Pull is:		
Grip (Knurled Se	ction) Finish	Options:		1 ¹ / ₄ " Dia.			
o US4/606	o US32D/630						
o 10BE/613E		o WSP					
 Stock Powder 	Coats (specify):					\bowtie	
Post/Ends Finish	Options:					\bowtie	
o US3/603	o US4/606					\bowtie	
o US32/629						\bowtie	Center to
o US10B/613		o BSP				\bowtie	Center
o WSP	Stock Powd	der Coats (specify): _			Overall		
Center to Center	(Maximum 24"): .		_		Height		
Overall Height (Maximum 36"):							
Door Type:	o Glass	o Metal	o Wood				
Door Thickness:	0 1/2"	0 1 ³ / ₄ "	o 2 1/4"				
	o Other:						Typical Cente of Post to
Hole Size (for glass of	door application o	nly):			\ _		End of Pull is 3
Mounting Type:	Thru Bolt (Metal/Wood Only)		Decorati	ve Thru Bolt		_	
	O Back to Back		Concealed (Metal/Wood Only)				
	 Concealed and Thru Bolt (Met 		tal/Wood Or	nly)			
Your signature indicates	the information c	ontained on this order	form is accura	te and ready to be	e manufactured.		
(customer signature)				(date)			

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424