Rockwood RM4154

ArborTek Series

Offset Pull - Round Ends



Experience a safer and more open world

| Complete this form | | orders.rockwoo | d@assaablo | y.com / or fax to | o: 800 922 9212 | | |
|--|---|---|-----------------------------------|-------------------------|------------------------------------|---|--|
| Customer Information Company Name: Account #: Email: Door #'s: | | | | Phone/Fax: PO #: | | | |
| Quantity: | | | | | | | |
| Post Finish Optio | ns: | US10B/613US32D/630 | | | → 1 ³ / ₄ "- | Projection 3" 1 1/2" Dia. | |
| Wood Type/Spec Domestic (Standard Premium: Super Premium: | ies Options:): O Hickory O Red Oak O Beech | White Oak Maple Cherry Canary | o Birch | | | Typical Center of Post to End of Pull is 3" | |
| Wood Finish Options: ○ Sanded Unfinished (Standard) ○ Clear ○ Dyed (Hickory only) ○ Tung Oil | | | | | Wood Grip | | |
| Center to Center | (Maximum 45 ¹ /2 "): | | | | | | |
| Overall Height (Maximum 48"): | | | | | Overall | Center | |
| Post Quantity: | ○ 2 (Standard) | | | | Height | to Center | |
| Post Length: | O Standard (1 ³/4") | | | | | | |
| Door Type: | Glass | o Metal | o Wood | | | | |
| Door Thickness: | o ¹/₂ " ○ Other: | 0 1 ³ / ₄ " | o 2 ¹ / ₄ " | | | 1" Dia. | |
| Hole Size (for glass door application only): | | | | | | | |
| Mounting Type: | Thru Bolt (Metal/Wood Only) Back to Back Concealed and Thru Bolt (Metal) | | Conceale | ealed (Metal/Wood Only) | | Typical Center of Post to End of Pull is 3" | |
| Your signature indicates (customer signature) | the information co | ontained on this orde | er form is accura | te and ready to be m | anufactured. | <u> </u> | |

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424