## Rockwood RM4110

## ArborTek Series

Straight Pull – Flat Ends



Experience a safer and more open world

Complete this form	n and email to: c	orders.rockwood	d@assaabloy	y.com / or fax to	800 922 9212	
Customer Informa	ation					
Company Name:						
Account #:						
						e #:
Door #'s:						
Quantity:						<del> </del>
<ul><li>US10B/613</li><li>US32D/630</li></ul>	<ul><li>US4/606</li><li>10BE/613E</li><li>BSP</li></ul>				Projection 3"	Post Len'gth 1 ³/4" ↓ 1 ¹/4" Dia.
Wood Type/Spec Domestic (Standard	a): O Hickory O Red Oak	<ul><li>Maple</li></ul>				Typical Center of Post to End of Pull is 3".
Premium: Super Premium:	<ul><li>Beech</li><li>Mahogany</li><li>Jatoba (Braz</li></ul>	∘ Canary	<ul><li>Birch</li><li>Walnut</li></ul>			1" Dia.
Wood Finish Options:  ○ Sanded Unfinished (Standard)  ○ Dyed (Hickory only)  ○ Clear  ○ Tung Oil					Wood Grip	Did.
Center to Center	(Maximum 45 <sup>3</sup> / <sub>4</sub> "):					
Overall Height (N	laximum 48"):		_		Overall	Center
Post Quantity:	○ 2 (Standard) Note: Mid Post recommended		o Other:	Other: for CTC greater than 42".		to Center
Post Length:	O Standard (1 ³/4")		o Other:			
Door Type:	o Glass	o Metal	o Wood			
Door Thickness:	o 1/2 <b>"</b> ○ Other:		o 2 <sup>1</sup> / <sub>4</sub> "		· · ·	
Hole Size (for glass	door application on	ly):			\\\'	1
Mounting Type:	<ul><li>Thru Bolt (Metal/Wood Only)</li><li>Back to Back</li><li>Concealed and Thru Bolt (Metal</li></ul>			e Thru Bolt d (Metal/Wood Only)	<u> </u>	Typical Center o Post to End of Pull is 3".
Your signature indicates	s the information co	ntained on this orde	er form is accurat	re and ready to be mo	inufactured.	
(customer signature)	·	·	_	(date)	-	

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424