## Rockwood RM6310

## Flush Leather Series

Straight Pull – Flat Ends



Experience a safer and more open world

| •  |  | o: orders.rockwa                  | ood@assaabloy.com          | / or fax to: 800 922 | 9212          |  |  |
|--|--|-----------------------------------|----------------------------|----------------------|---------------|--|--|
| Customer Informa   |  |                                   | D. I.                      |                      |               |  |  |
| Company Name:  |  |                                   | Date                       | - /F                 | /             |  |  |
| Account #:Email:   |  |                                   |                            |                      |               |  |  |
|  |  |                                   | PO#                        |                      |               |  |  |
| D001 # 3   |  |                                   |                            |                      |               |  |  |
| Quantity:  |  |                                   |                            | <del>_</del>         |               | - <del>-</del>                               |  |
| ○ 10BE/613E  | <ul><li>US4/606</li><li>US32/629</li></ul>   | o US32D/63                        | ○ US10B/613<br>80 ○ BSP    | Projecti<br>3"<br>   | on   Post Le  |  |  |
| Leather Type/Co English Bridle Lo O BLK (Black) LBRN (Light Br Upholstery Leat U-DBRN (Dar                                 | eather:  o Erown)  o N  cher:  |                                   | O DBRN (Dark Brown<br>own) |                      | 5/8"<br>(^_)  | of Post to End<br>of Pull is 3".             |  |
| Center to Center   | (Maximum 90"):   | ·                                 |                            |                      |               | Grip   |  |
| Overall Height (M<br>Note: Maximu  |  |                                   |                            |                      |               |  |  |
| Post Quantity: 0 2 (Standard)  Note: Mid Post recommended for CTC greater 73" (Brass/Bronze), 90" (Aluminum), 90" (Stainle |  |                                   | er than                    | Overal<br>Height     |               | Center<br>to<br>Center                       |  |
| Post Length:   | <ul><li>Standard</li></ul>   | (1 <sup>3</sup> / <sub>4</sub> ") | o Other:                   |                      |               |  |  |
| Door Type:   | <ul><li>Glass</li></ul>  | <ul><li>Metal</li></ul>           | ∘ Wood                     |                      |               |  |  |
| Door Thickness:  | o 1/2 <b>"</b><br>o Other:   |                                   | 0 2 1/4"                   |                      |               |  |  |
| Hole Size (for glass   | door application   | only):                            |                            |                      |               |  |  |
| Mounting Type:   | Aounting Type:  O Thru Bolt (Metal/Wood Only) O Back to Back O Concealed and Thru Bolt (Me |                                   |                            | Bolt<br>I/Wood Only) |               | 1" Dia.                                      |  |
| Your signature indicates is accurate and ready t   |  |                                   | rder form                  | 3 5                  | 5/8"<br> <br> | Typical Center of Post to End of Pull is 3". |  |
| (customer signature)   |  |                                   | (date)                     |                      |               |  |  |

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424