Rockwood RM7810

ROCKWOOD ASSA ABLOY

GeoMetek Diamond Pull Series

Diamond Ends - Square Posts

Experience a safer and more open world

Complete this fo	rm and email	to: orders.rockw	ood@assaabloy.co	m / or fax to: 8	00.922.9212		
Customer Infor	mation						
Company Name:				_ Date:			
Account #:			Ph	one/Fax:		/	
Email:			PC) #:	Line #:		
Door #'s:							
Quantity:				1 3/4"		Typical	
Finish Options	•		Projection: 2 ¹³ / ₁₆ "			Center of Pos to End of Pull	
o 10BE/613E	o US32/62	9 • US32D/63	0			is 3"	
	∘ US32DN	1S				′ ₄ "	
	o WSP		$^{3}/_{4}^{\parallel} \times ^{3}/_{4}^{\parallel}$,		1	
O Stock Pow	der Coats (speci	fy):					
Center to Cent	er (Maximum 115	"):					
Overall Height	(Maximum 120"):			Ove Heiç			
Post Quantity:	o 2 (Standar	rd) Othe	r:	*Minin	num	Center to	
Note: Mid F	ost recommen	nded for CTC gree	ater than 62".	betwee and OA	n CTC	Center	
Door Type:	o Glass	o Metal	o Wood	be 2 ¹ / each	2" on		
Door Thickness	s: 0 1/2"	○ 1 ³/₄"	o 2 ¹ / ₄ "				
	o Other:						
Hole Size (for glo	ıss door applicatic	on only):					
Mounting Type	:						
Thru Bolt (Metal/Wood Only)					[-4-]		
	•	tal/Wood Only)				Typical Center of Pos	
Back to Back		0.13				to End of Pul	
	d (Metal/Wood	Only) (Metal/Wood On	W		$ \qquad \forall \nearrow $	is 3"	
			••	_ ¥	-	V *	
Your signature indica	ates the information	on contained on this c	order form is accurate an	d ready to be manu	ufactured.		
)			(date)			

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424