## ORDER FORM

## Rockwood RM7805 GeoMetek Diamond Pull Series

Complete this form and email to: orders.rockwood@assaabloy.com / or fax to: 800.922.9212

Flat Ends - Diamond Posts

<b>Customer Inform</b>	nation								
Company Name:				Date:					
Account #:									
Email:				PO #:		L	ine #:		
Door #'s:				-					
Quantity:			-		<u>→</u>		Γ	Typico	
<ul><li>○ US32MS</li><li>○ BSP</li></ul>	○ US32DMS ○ WSP	o US32D/630	-	jection: <sup>2 13</sup> /16" 3/4"	× <sup>3</sup> /4"		1 <sup>1</sup> / <sub>16</sub> "	Center of to End of is 3"	
Center to Cente	<b>r</b> (Maximum 119") <b>:</b>								
Overall Height (/	Maximum 120"):				Overall Height *Minimum				
Post Quantity:       0 2 (Standard)       0 Other:         Note:       Mid Post recommended for CTC greater than 62".					difference Cent between CTC Cer and OA can be 1/2" on				
Door Type:	<ul> <li>Glass</li> </ul>	<ul> <li>Metal</li> </ul>	° Wood		each end				
Door Thickness:	o 1/2" o Other:		○ 2 <sup>1</sup> /4"						
Hole Size (for glass	s door application o	nly):							
Mounting Type: • Thru Bolt (Metal/Wood Only) • Decorative Thru Bolt (Metal/Wood Only)								Typico	

Back to Back

Concealed (Metal/Wood Only)

• Concealed and Thru Bolt (Metal/Wood Only)

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

(date)

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424

Copyright © 2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.

to End of Pull

is 3"



Experience a safer and more open world