Rockwood RM7940

GeoMetek Series

Straight Pull - Square Ends



Experience a safer and more open world

Customer Information		
Company Name:		
Account #:	Phone/Fax: /	
Email:	PO #: Line #	# :
Door #'s:	_	
Quantity:		
Finish Options:	3"	1 1/4"
 ○ 10BE/613E ○ US32/629 ○ US32D/630 ○ US32MS ○ US32DMS ○ BSP ○ WSP 		
Stock Powder Coats (specify):		
Center to Center (Maximum 118 3/4"):	11/4" → ← →	← 1 ¹/₄"
Post Quantity: • 2 (Standard) • Other: Note: Mid Post recommended for CTC greater than 108 Door Type: • Glass • Metal • Wood	. Overall	Center
Door Thickness: ○ 1/2"	Height	Cente
Hole Size (for glass door application only):		
Mounting Type: o Thru Bolt (Metal/Wood Only) Decorative Thru Bolt (Metal/Wood Only)		
O Back to Back		[]
 Concealed (Metal/Wood Only) 	<u> </u>	
 Concealed and Thru Bolt (Metal/Wood Only) 		
Your signature indicates the information contained on this order form is acc	urate and ready to be manufactured.	
(customer signature)	 (date)	

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424