Rockwood RM7935

GeoMetek Pull Series

Offset Pull - Rectangular Bridge



Experience a safer and more open world

| Company Name: | Date: | | |
|--|--------------------------------------|-------------------------------------|-----------------------|
| Account #: | | | |
| Email: | | | |
| Door #'s: | | LINE # | |
| D001 # 5. | | | |
| Quantity: | 1 1/2" | 3"i | · * · |
| Finish Ontions | | | Typical nter of Po |
| Finish Options: • 10BE/613E • US32/629 • US32D/630 | 3 1/4" | | End of Pu |
| • US32MS • US32DMS | | | is 3" |
| o BSP o WSP | | | <u></u> + |
| Stock Powder Coats (specify): | | | _ |
| | | 3/4" | |
| Center to Center (Maximum 118 1/4"): | | Overall Height | |
| Overall Height (Maximum 120"): | | *Minimum difference between | |
| Post Quantity: o 2 (Standard) o Other: Note: Mid Post recommended for CTC greater than | | CTC and OA can be 7/6" on each end. | Center to Center |
| Door Type: • Glass • Metal • Wo | pod | | |
| Door Thickness: ○ 1/2" | ' ₄ " 3/ ₄ " → | ← → ← 1 ¹ / | '2" |
| Hole Size (for glass door application only): | | | |
| Mounting Type: | | | _ |
| Thru Bolt (Metal/Wood Only) | |) D | == |
| Decorative Thru Bolt (Metal/Wood Only) | | | Typical nter of Po |
| ○ Back to Back | | | End of Pu |
| Concealed (Metal/Wood Only) | | | is 3" |
| Concealed and Thru Bolt (Metal/Wood Only) | | | · ¥ |
| Your signature indicates the information contained on this order form i | s accurate and ready to be manuf | actured. | |
| | , | | |
| | | | |

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424