Rockwood RM7930

GeoMetek Series

Offset Pull - Rectangular Ends



Experience a safer and more open world

Complete this form and email to: orders.rockwood@assaab	oloy.com / or fax to: 8	300.922.9212	
Customer Information			
Company Name:	Date:		
Account #:	Phone/Fax:	//	
Email:			
Door #'s:			
Quantity: 1½"	 		3/4"
Finish Options: o 10BE/613E o US32/629 o US32D/630 o US32MS o US32DMS o BSP o WSP o Stock Powder Coats (specify):	3 1/4"	→ 3/4" →	
Center to Center (Maximum 119 1/4"):			1 /2
Post Quantity: • 2 (Standard) • Other: Note: Mid Post recommended for CTC greater than 110".	Overall Height		Center t Center
Door Type: • Glass • Metal • Wood	Tieigiii		Cernel
Door Thickness: ○ ¹/₂"			
Hole Size (for glass door application only):			
Mounting Type: o Thru Bolt (Metal/Wood Only) o Decorative Thru Bolt (Metal/Wood Only) o Back to Back o Concealed (Metal/Wood Only) o Concealed and Thru Bolt (Metal/Wood Only)			
Your signature indicates the information contained on this order form is accu	urate and ready to be manu	ufactured.	
(customer signature)	(date)		

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424