Rockwood RM7907

GeoMetek Series

Straight Pull - Square Ends



Experience a safer and more open world

	Date:	
Account #:		/
Email:		
Door #'s:		
Quantity:		2 3/4"
Finish Options:		
 10BE/613E US32/629 US32D/630 US32MS US32DMS BSP WSP Stock Powder Coats (specify): 		
Center to Center (Maximum 119"):	1"	→ ←1"
Post Quantity: ○ 2 (Standard) ○ Other: Note: Mid Post recommended for CTC greater than		
Door Type: • Glass • Metal • Wo	pod	
Door Thickness: $0.1/2$ " $0.13/4$ " $0.21/2$ "	′ ¹¹	Center t Center
Door Thickness: ○ 1/2"		
Other:		
Other: Hole Size (for glass door application only):		
Other: Hole Size (for glass door application only): Mounting Type: Thru Bolt (Metal/Wood Only)		
Other: Hole Size (for glass door application only): Mounting Type: Thru Bolt (Metal/Wood Only) Decorative Thru Bolt (Metal/Wood Only)		
Other: Hole Size (for glass door application only): Mounting Type: O Thru Bolt (Metal/Wood Only) Decorative Thru Bolt (Metal/Wood Only) Back to Back		
Other: Hole Size (for glass door application only): Mounting Type: Thru Bolt (Metal/Wood Only) Decorative Thru Bolt (Metal/Wood Only)		

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424