Rockwood RM7855

ROCKWOOD ASSA ABLOY

GeoMetek Diamond Pull Series

Diamond Ends - Diamond Posts

Experience a safer and more open world

Complete this form	n and email to:	orders.rockwa	ood@assaablo	y.com / or fo	ax to: 800.922	.9212	
Customer Inform	ation						
Company Name:				Date:			
Account #:				Phone/Fax:		/	
Email:				PO #:		Line #:	
Door #'s:							
Quantity:							Typical
Finish Options:			Project 3 ⁵ / ₃₂	ion:			Center of Pos to End of Pul
•	o US32/629	o US32D/63					is 3"
	o US32DMS					1 ¹³ / ₃₂ "	<u> </u>
o BSP	o WSP			1" × 1"		1 7 7 1	<u> </u>
 Stock Powde 	er Coats (specify):						
Center to Center	' (Maximum 114 ¹ / ₄ "):					
Overall Height (M	1aximum 120") :				Overall Height		
Post Quantity: Note: Mid Pos	○ 2 (Standard) st recommende				*Minimum difference between CTC and OA can		Center to Center
Door Type:	o Glass	o Metal	o Wood		be 2 1/8" on each end.		
Door Thickness:	o 1/2" o Other:		o 2 ¹ / ₄ "				
Hole Size (for glass	door application o	only):					
Mounting Type:							
	etal/Wood Only	<i>'</i>)			\		1
Decorative T	hru Bolt (Metal	/Wood Only)					Typical
 Back to Back 							Center of Pos to End of Pu
-	Metal/Wood Or	, -					is 3"
 Concealed o 	ınd Thru Bolt (M	Netal/Wood Onl	у)				U
Your signature indicate	s the information o	contained on this o	rder form is accura	ite and ready to l	be manufactured		
(customer signature)				(date)			

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424