Rockwood RM7850

ROCKWOOD ASSA ABLOY

GeoMetek Diamond Pull Series

Diamond Ends - Square Posts

Experience a safer and more open world

Company Name: Account #: Email: Door #'s:							
Email:				Phone/Fax:		/	
	Email:						
Quantity:	·····			13	/ ₄ "		Typical
○ US32MS○ BSP	US32DMSWSP	• US32D/630 S		Projection: 3 5/32" 1" x 1"		1"	Center of P to End of F is 3"
Center to Center	(Maximum 114 ¹ /	4") •					
Overall Height (A	Лахітит 120") : _				Overall		
Post Quantity: • 2 (Standard) • Other: Note: Mid Post recommended for CTC greater than 85".					Height *Minimum difference between CTC		Center to
Door Type:	o Glass	o Metal	o Wood		and OA can be 2 ⁷ /8" on each end.		
Door Thickness:	o 1/2" o Other:		o 2 ¹ / ₄ "				
Hole Size (for glass	door application	only):					
Mounting Type: • Thru Bolt (M • Decorative T • Back to Back • Concealed (• Concealed c	Thru Bolt (Meta < Metal/Wood C	I/Wood Only)					Typical Center of P to End of F is 3"

Rockwood Manufacturing Company 300 Main St. Rockwood, PA 15557 www.rockwoodmfg.com 1 800 458 2424