## Mortise Deadlock

**Backset:** Available with  $2^{3}/4^{11}$  backset only.

 $1\frac{3}{4}$ " thick with  $4\frac{1}{2}$ " minimum stile as standard. Doors:

For doors over 13/4" thick, please specify door

thickness.

Case: Heavy wrought steel with zinc dichromate finish

for corrosion resistance. 4" w x 3" h

Adjustable armored steel front, with 11/8" w x Front:

45/8" h solid brass or stainless steel faceplate

for all lock bodies.

**Deadbolt:** 1" proj.  $x \frac{5}{8}$ " thick  $x \frac{1}{16}$ " h full throw stainless steel.

High carbon steel. Springs:

Strike: Solid brass or stainless steel strike plate.  $1\frac{1}{8}$ " w x  $3\frac{1}{2}$ " h

Cylinder: Solid brass from bar stock. Made in USA. Schlage®

"C" keyway supplied as standard, with two OMNIA nickel silver keys. When applicable, cylinder collars are supplied

with compression spring. Available on special orders with a variety of other keyways and key combinations.

Specify Keyed Alike (KA) when needed. Master/Grand/Construction keying available at additional cost. Keying:







DESCRIPTION	US3 US26 US26D	US15 US10B SB
041/N Standard Cyl. x T/P	\$238	\$245
041/NAC Double Cylinder	260	265
041/NE T/P One Side Only	216	224
041/NC Cyl. One Side Only	225	228

- 4 <sup>1</sup>/<sub>16</sub>" -

15/32"

Interior

Turnpiece Hole

45/8" q

of Lock

Exterior Cylinder

Hole

23/32"







DESCRIPTION	US3 US26 US26D	US14 US15 US10B	US32D
041M/N Standard Cyl. x T/P	\$237	\$244	\$269
041M/NAC Double Cylinder	260	267	294
041M/NE T/P One Side Only	201	207	228
041M/NC Cyl. One Side Only	225	228	250

041MS





DESCRIPTION	US26 US26D	US14 US15 US10B
041MS/N Standard Cyl. x T/P	\$266	\$275
041MS/NAC Double Cylinder	288	301
041MS/NE T/P One Side Only	220	226
041MS/NC Cyl. One Side Only	242	251

Suggested retail prices effective January 1, 2019.