CS WallMount Track



The Pocket Door Experts

Item	Description	Length	Code
D 12	CS WallMount Track Kit	6ft	TSWMNA-6
	(including fascia and end caps)	8ft	TSWMNA-8
		12ft	TSWMNA-12
	Suits 1-3/8" to 1-3/4" door thickness	24ft	TSWMNA-24
A	Natural (Clear) Anodized	Custom	TSWMNA-NSS
	CS WallMount Track Kit	6ft	TSWMBA-6
	(including fascia and end caps)	8ft	TSWMBA-8
	Suits 1-3/8" to 1-3/4" door thickness	12ft	TSWMBA-12
4	· ·	24ft	TSWMBA-24
	Bronze Anodized	Custom	TSWMBA-NSS
54	CS WallMount Track (Carriage Section only)	Custom	ZA00244
A A	M6 (200lb) with no stops		DKM0601
A A A	M6 (200lb) with 1 stop		DKM0611
•	M6 (200lb) with 2 stops		DKM0621
	M8 (500lb) with no stops		DKM0801
	M8 (500lb) with 1 stop	DKM0811	
	M8 (500lb) with 2 stops	DKM0821	
	Sofstop Single Action 0 - 176 lb with no stops		DKS0301
	Sofstop Single Action 0 - 176 lb with 1 stop		DKS0311
	Sofstop Single Action 0 - 176 lb with 2 stops		DKS0321
	Sofstop Single Action 176 - 264 lb with no stops		DKS0401
	Sofstop Single Action 176 - 264 lb with 1 stop		DKS0411
	Sofstop Single Action 176 - 264 lb wi	DKS0421	
	Sofstop Twin Double Action 0 - 176 II	DKS0601	
	Sofstop Twin Double Action 0 - 176 II	DKS0611	
	Sofstop Twin Double Action 0 - 176 II	DKS0621	
NO.			

	SofStop® Single	Minimum Door Width		
Soft Close		No stop	1 Stop	2 Stops
	0 - 176lb 80kg	25"(635mm)	28"(711mm)	30"(762mm)
	176-264lb 120kg	28"(711mm)	31"(787mm)	33"(838mm)

SofStop® Twin		Minimum Door Width		
		No stop	1 Stop	2 Stops
176		33" (840mm)	36" (914mm)	39" (990mm)

All copyright and other property in this document is reserved by Cavity Sliders USA Inc. Details and specifications are subject to change without notice. Whilst all care is taken to ensure the accuracy of all information, no responsibility will be accepted for any errors or omissions.

Drawings & pictures are not to scale. All dimensions in inches (and mm). 61319/16 10.2019